Job name . . . . : QDBSRV05   User . . . . :   QSYS   Number . . . . :   013892
Job description . . . . . . : *SYS   Library . . . . . :

MSGID	TYPE	SEV	DATE	TIME	FROM PGM	LIBRARY	INST	TO PGM	LIBRARY	INST
CPF1124	Information	00	19/01/09	21:05:08.056496	QWCINIPP	QSYS	02FD	*EXT		*N

Message . . . . :   Job 013892/QSYS/QDBSRV05 started on 19/01/09 at 21:05:07
in subsystem *NONE in *NONE. Job entered system on 19/01/09 at 21:05:07.

MSGID	TYPE	SEV	DATE	TIME	FROM PGM	LIBRARY	INST	TO PGM	LIBRARY	INST
SQL0601	Diagnostic	30	19/01/09	21:23:13.435392	QSQCRTI	QSYS	*STMT	QSQCRTI	QSYS	*STMT

From module . . . . :   QSQCRTI
From procedure . . . . . . :   CLEANUP
Statement . . . . :   8582
To module . . . . :   QSQCRTI
To procedure . . . . :   CLEANUP
Statement . . . . :   8582
Message . . . . :   SYSIXADVI in QSYS2 type *FILE already exists.
Cause . . . . . :   An attempt was made to create SYSIXADVI in QSYS2 or to
rename a table, view, alias, or index to SYSIXADVI, but SYSIXADVI already
exists. All tables, views, aliases, indexes, SQL packages, sequences,
constraints, triggers, and user-defined types in the same schema must have
unique names. -- If SYSIXADVI is a temporary table, it cannot be replaced
unless the WITH REPLACE clause is specified. -- If the schema name is *N,
this is a CREATE SCHEMA statement. If this is a CREATE TABLE or ALTER TABLE
statement and the type is *N, SYSIXADVI is a constraint. Recovery . . . :
Change SYSIXADVI to a name that does not exist, or delete, move, or rename
the existing object. If this is a temporary table, use the WITH REPLACE
clause. If creating an SQL package, specify REPLACE{*YES} on CRTSQLPKG. Try
the request again.

MSGID	TYPE	SEV	DATE	TIME	FROM PGM	LIBRARY	INST	TO PGM	LIBRARY	INST
CPF9898	Information	40	19/01/09	21:23:13.481592	QSQADVIC	QSYS	*STMT	QDBSERVE	QSYS	0072

From module . . . . :   QSQADVIC
From procedure . . . . . . :   DUMP_EVENT_DATA_TO_JOBLOG
Statement . . . . :   1135
Message . . . . :   INDEX EVENT: Table name=SYSIXADV Short name=SYSIXADV
Schema name=QSYS2   Table size=0000000036 Index type=RADIX
Reason for Index=I1 Timestamp of advice=2009-01-19-21.23.00.069935 Est. for
Create Index{secs}=0000000001 Est. of query{secs}=0000000001 Advice
Count=0000000001 Page Size{K}=0000000064 Key Columns=KEY_COLUMNS_ADVISED,
LEADING_COLUMN_KEYS, TABLE_NAME, TABLE_SCHEMA, NLSS_TABLE_SCHEMA,
INDEX_TYPE, NLSS_TABLE_NAME Leading Keys=KEY_COLUMNS_ADVISED,
LEADING_COLUMN_KEYS, TABLE_NAME, TABLE_S
Cause . . . . . :   This message is used by application programs as a general
escape message.

MSGID	TYPE	SEV	DATE	TIME	FROM PGM	LIBRARY	INST	TO PGM	LIBRARY	INST
CPF1164	Completion	00	20/01/09	00:08:13.917624	QWTMCEOJ	QSYS	00D7	*EXT		*N

Message . . . . :   Job 013892/QSYS/QDBSRV05 ended on 20/01/09 at 00:08:13; 4
seconds used; end code 0 .
Cause . . . . . :   Job 013892/QSYS/QDBSRV05 completed on 20/01/09 at 00:08:13
after it used 4 seconds processing unit time. The job had ending code 0.
The job ended after 1 routing steps with a secondary ending code of 0. The
job ending codes and their meanings are as follows: 0 - The job completed
normally. 10 - The job completed normally during controlled ending or
controlled subsystem ending. 20 - The job exceeded end severity {ENDSEV job
attribute}. 30 - The job ended abnormally. 40 - The job ended before
becoming active. 50 - The job ended while the job was active. 60 - The
subsystem ended abnormally while the job was active. 70 - The system ended
abnormally while the job was active. 80 - The job ended {ENDJOBABN command}.
90 - The job was forced to end after the time limit ended {ENDJOBABN
command}. Recovery . . . :   For more information, see the Work Management

  Job name . . . . : QDBSRV05   User . . . . . . :   QSYS   Number . . . . :   013892
  Job description . . . . . . : *SYS   Library . . . . . :

MSGID   TYPE   SEV DATE   TIME   FROM PGM   LIBRARY   INST   TO PGM   LIBRARY   INST
                      topic in the Information Center,
                      http://www.ibm.com/eserver/iseries/infocenter.